

---

## HALOSTAR 10 W 12 V G4

HALOSTAR STARLITE | Low-voltage halogen lamps with pin base and axial filament



---

### Areas of application

- General illumination
- Entrance lighting
- Accent lighting
- Lighting for reading
- Garden lighting
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings

---

### Product benefits

- Brilliant accent light
- Incredibly small dimensions for revolutionary new luminaire designs
- Approved for use in open luminaires (to IEC 60598-1)
- Axial filament for optimum directional light
- Special pins for corrosion protection
- UV filter
- Contains no mercury

---

### Product features

- Average life: 4,000 h
- 100 % dimmable
- Color rendering index  $R_a$ : 100

# Product datasheet

## Technical data

### Electrical data

Nominal wattage	10.00 W
Nominal voltage	12 V
Rated wattage	10.00 W
Power factor $\lambda$	1.00


### Photometrical data

Nominal luminous flux	130 lm
Color temperature	2800 K
Light color as per EN 12464-1	Warm White
Rated luminous flux	130 lm
Color rendering index Ra	100
Lumen main.fact.at end of nom.life time	0.80

### Light technical data

Starting time	0.0 s
Warm-up time (60 %)	0.00 s

### Dimensions & weight



Diameter	10.0 mm
Overall length	33.0 mm
Light center length (LCL)	22.0 mm
Length	33.0 mm
Outer bulb	T10

### Lifespan

Nominal lamp life time	4000 h
------------------------	--------

## Product datasheet

<b>Rated lamp life time</b>	4000 h
<b>Number of switching cycles</b>	100000 <sup>1)</sup>

<sup>1)</sup> At 1 min on / 3 min off

### Additional product data

<b>Base (standard designation)</b>	G4
<b>Lamp mercury content</b>	0.0 mg
<b>Mercury-free</b>	Yes

### Capabilities

<b>Burning position</b>	Any
<b>Dimmable</b>	Yes

### Certificates & standards

<b>Energy efficiency class</b>	C
<b>Energy consumption</b>	11 kWh/1000h


### Country specific categorizations

<b>ILCOS</b>	HSGST/C/UB-10-12-G4-10/22
<b>Order reference</b>	64415 S AX 10W

# Product datasheet

## Light Distribution

---



## Spectral power distribution

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300335087	HALOSTAR 10 W 12 V G4	Shipping carton box 40	144 mm x 107 mm x 121 mm	1.86 dm <sup>3</sup>	202.67 g

---

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.