

LED GARDEN SPIKE KIT

Product Features

- Easy plug and play 'do-it-yourself' install using push and fit connectors and 12V adaptor
- Latest integrated LED spike with high impact housing, tilt and rotatable head and tough hard wearing H05RN-F rubber cable
- Add extra LED spikes to your circuit for added coverage - 8 spikes maximum
- 1.8 metre spacing as standard - easy to add 2 metre extension cable for increased spacing



IP65 Rating Spike & Cable	IP20 Rating Adaptor	30K Hours	4000K NEUTRAL WHITE	BLACK FINISH	2 YEAR Warranty
-------------------------------------	-------------------------------	------------------	----------------------------	---------------------	------------------------



CAT NO.	LUMINAIRE LUMENS	WATTAGE
LEXGSPK4P40	200 Per Spike	3W Per Spike

Kit Contains:

1 x Starter Spike, 2 x Mid-Ext Spikes, 1 x End Spike, 1 x 12V Adaptor

Product Accessories

CAT NO.	DESCRIPTION
LEXGSPK1P40	Single Mid-Extension Spike
LEXGSPK2M	2 Metre Extension Cable

Product Accessories



Optional Extensions	
EXTENSION CABLE 2 metre 	
<p>Extend distance between adaptor to Starter Spike max. 5x extension cables (10 metres total)</p>	<p>Extend distance between Spike Lights max. 1x extension cable (2 metres total)</p>
SINGLE PACK Mid-extension spike 	<p>Add LED Spike Lights to your 4 pack, install 8 spikes maximum total (extension spike cannot be added to end spike, add earlier in circuit)</p>



CAT NO.	LLM/W	CRI	FREQUENCY (Hz)	IK RATING	TEMP RANGE (°C)	AMBIENT TEMP RATED LIFE (°C)	L/B RATED LIFE
LEXGSPK4P40	66	>80	50-60	IK04	-20 to +40	25	L70/B50

BG and Masterplug products that can be used with LED

WP23L	WBXBFG8BTMS24
Nexus Storm Unswitched Weatherproof Socket Outlet Large Housing 1-Gang 13A	Lockable IP54 weatherproof enclosure extension lead and timer
<ul style="list-style-type: none"> Large housed outdoor socket that fits the transformer style plug of the LED spike kit IP66 Rated with plug in use, cover sealed Terminal capacity 3 x 2.5mm², 3 x 4.0mm² & 2 x 6.0mm² Supplied with multiple knock-out mounting box 13A sockets manufactured to BS 1363-2  	<ul style="list-style-type: none"> Portable weatherproof box with extension lead for simple set-up with the LED spike kit Extension Lead with Weatherproof Socket 8 metre cable Weatherproof box   

STANDARD	DESCRIPTION
60598-1	Luminaires – General requirements
60598-2-4	Luminaires – Portable
61000-3-2	Electromagnetic compatibility (EMC) - Part 3-2: Limits – for harmonic current emissions
61000-3-3	Lamp controlgear – Part 1: General and safety requirements
61547	Equipment for general lighting purposes – EMC immunity requirements
55015	Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment

LUCECO

 This luminaire contains built-in LED lamps.

A++
A+
A
~~B~~
~~C~~
~~D~~
~~E~~

} LED

The lamps cannot be changed in the luminaire.

874/2012 

