

MASTER PL-T 2 Pin

MASTER PL-T 18W/830/2P 1CT

MASTER PL-T is an efficient compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications demanding higher lighting levels. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base.

Product data

• General Characteristics

Cap-Base Cap-Base Information Life to 10% failures FM	GX24d-2 2P 6500 hr
Life to 50% failures	10000 hr
LSF EM 2000h Rated, 3h cycle	99 %
LSF EM 4000h Rated,	98 %
3h cycle LSF EM 6000h Rated,	92 %
3h cycle LSF EM 8000h Rated, 3h cycle	78 %

• Light Technical Characteristics

0	
Color Code	830 [CCT of 3000K]
Color Rendering	82 Ra8
Index	
Color Designation	Warm White
(text)	
Color Temperature	3000 K
Luminous Flux EM	1200 Lm
25°C, Rated	
Luminous Flux EM	1200 Lm
25°C, Nominal	
Lum Efficacy Rated	67 (min) Lm/W
EM 25°C	
LLMF EM 2000h	92 %
Rated	07.0/
LLMF EM 4000h	87 %
Rated	
LLMF EM 6000h	84 %
Rated	

LLMF EM 8000h	81 %
Rated	
Design Temperature	28 C
Chromaticity Coor-	434 -
dinate X	
Chromaticity Coor-	397 -
dinate Y	

• Electrical Characteristics

Lamp Wattage	18 W	
Lamp Wattage EM	18 W	
25°C, Nominal		
Lamp Wattage EM	18.0 W	
25°C, Rated		
Lamp Voltage EM	100 V	
25°C		
Lamp Current EM	0.225 A	
25°C		
Dimmable	No	

• Environmental Characteristics

Energy Efficiency	В
Label (EEL)	
Mercury (Hg)	1.4 mg
Content	
Energy consumption	22 kWh
kWh/1000h	

• Product Dimensions

Base Face to Base	71.8 (max) mm
Face A	
Insertion Length B	96.0 (max) mm
Overall Length C	119.2 (max) mm
Diameter D	41 (max) mm



MASTER PL-T 2 Pin

• Product Data

Order code 927914383071 Full product code 927914383071

Full product name MASTER PL-T 18W/830/2P 1CT
Order product name MASTER PL-T 18W/830/2P 1CT/

5X10CC


Pieces per pack 1
Packing configuration 5X10CC
Packs per outerbox 50


Warnings and Safety • Dir

• Use only with electromagnetic control gear

 Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position

Dimensional drawing





Bar code on pack - 8711500610508

EAN1

Bar code on intermediate packing - 8711500610515

EAN2

Bar code on 8711500610591

outerbox - EAN3

Logistic code(s) - 927914383071

12NC

ILCOS code FSM-18/30/1B-I-GX24d=2

Net weight per piece 59.000 gr


• Dimming is not possible

MASTER PL-T 18W/830/2P 1CT

Product	A (Max)	B (Max)	C (Max)	D (Max)
PL-T 18W/830/2P M	71.8	96.0	119.2	41

MASTER PL-T 2 Pin

Photometric data





© 2014 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.